


Geotone JuickLay

LOOSE LAY RESILIENT FLOORING





Geotone SuickLay

Loose Lay flooring, aSustainable solution forQuick Turnaround projects

Introducing Geotone QuickLay, the latest addition to the loose lay family of innovative floor coverings from Polyflor.

A premium, versatile and practical solution, ideal for quick turnaround projects, adhesive-free Geotone QuickLay combines **Easy Fit Technology**, **Low Maintenance** benefits and is optimised for **Sustainable Performance**.

Available in $2m \times 20m$ rolls, Geotone QuickLay enables busy public spaces to be reoccupied and ready for use again on the same day, thus minimising downtime and disruption to services and facilities.

Visually, the **design** concept for Geotone QuickLay centres around a common colour scheme, taking inspiration from elements found in the natural world, including pebbles and stones, often linked to forms of wellbeing & comfort.


With a subtle texture and matt finish, for a consistent overall appearance and ideal for open-plan spaces when a unified and cohesive look is required, the cool & fresh, warm & soothing tone-on-tone palette of Geotone QuickLay evokes a sense of calm and rejuvenation within any interior design scheme.

Continuing Polyflor's commitment to the Health & Care sector, Geotone QuickLay is a Dementia Design Accredited Product via the University of Stirling (see page 9 for DSDC ratings by shade), promoting more positive and inclusive environments for those living with a dementia.

Why choose

Geotone SuickLay

Rewriting the rules for laying sheet flooring, without the need for compromise in terms of performance & quality or design & decoration, adhesive-free Geotone QuickLay is an efficient and effective solution that allows busy spaces to get back to business as normal, quickly.





emissions



Superior cleanability



installation





Lay over subfloors up to 97% RH for a seamless finish



Suitable for high traffic areas



100% recyclable & reusable



Easy Fit Technology

12 steps to the perfect Geotone QuickLay installation

Receipt & Storage

On arrival at site, check colours correspond, quantities are correct and that there are no signs of damage.

The rolls should be safely secured in an upright position and stored at a minimum temperature of 18°C for at least 24 hours prior to installation.

Conditioning


Geotone QuickLay requires conditioning ahead of installation, this should be carried out in the same area as the installation to prevent thermally induced dimensional changes.



Apply the QuickLay double-sided tape



around the perimeter of the room and at any doorways, set 2mm away from the edge of



Product Handling

differences.

Check you are happy with the positioning of the flooring and the measurements are



Geotone QuickLay can be hot welded at the seams and to coved skirtings upon immediate



Standard installation tools. Only Polyflor QuickLay recommended double-sided tape should be used.



Measure 37.5mm away from the side of the seam and mark with a straight edge or chalk line.



Carefully peel away the protective film from all areas where the tape has been applied.



Sweep or vacuum the floor area, check the

condition of the subfloor and make good as

necessary. If the substrate is highly porous a

suitable primer may be required.

Apply the QuickLay double-sided tape along the marked seams.



Once complete, place the floor covering into position ensuring a 'neat fit'.




To ensure the QuickLay tape is firmly

a hand roller or cork board.


positioned correctly, simply press down with

A hand roller or heavy roller can be used at all seams/perimeter immediately after installing to ensure sufficient contact has been made.






Geotone QuickLay in the room. Allow a 25mm overlap at the seams and cut in to form a





completion of the installation.



Designed to support health & wellbeing

Research shows there are more than 944,000 people in the UK who are living with a dementia. 1 in 11 people over the age of 65 have a dementia in the UK.

The number of people with a dementia is increasing because people are living longer. It is estimated that by 2030, the number of people with a dementia in the UK will be more than 1 million. (NHS https://www.nhs.uk/conditions/dementia/about-dementia/

what-is-dementia/)

Emphasis on designing interiors that are inclusive, future proofed


and dementia-friendly, to help promote a more positive environment

that impacts on health and wellbeing, whether within an assisted living facility, for people living at home or staying in hospital, has never been greater.

Choosing the right flooring is key to promoting a more positive and inclusive environment for those living with a dementia.

Polyflor has devised the following 10 principles which reference back to the overarching principles within Health Building Note HBN 08-02, Design Principles for a Dementia-Friendly Environment, here in relation to Geotone QuickLay.

Polyflor: Principles for Dementia-Friendly Flooring	Geotone QuickLay PUR: Designed to promote harmony & wellbeing
1: Develop one continuous flooring surface	The floor can be both seen and experienced as one continuous surface as Geotone QuickLay is a flexible resilient sheet vinyl, in rolls 2m wide by 20m in length that can be installed in large sections.
	Geotone QuickLay can be welded and walked upon immediately, creating an overall cohesive appearance.
2: Careful use of tonal contrast	As a rule of thumb, the light reflectance value (LRV) should be 30 points difference between surfaces to get good tonal contrast.
	LRVs range from 10 to 64 enabling tonal contrast with other surfaces, fixtures & fittings.
3: Reduce impact sound	A well-planned acoustic environment enhances the feeling of privacy, safety and comfort.
	With an Impact Sound Reduction value of 6dB, Geotone QuickLay can contribute to reducing background or reverberation sound within a room. Less noise disturbance is generated through loose lay installation methods.
4: Accentuate colours to give depth	Geotone QuickLay features a selection of light, mid & darker shades which can help in the perception of the size and shape of a room to aid wayfinding.
5: Avoid sensory overload and false steps	Flooring which contributes to sensory overload can confuse the eye and cause a person living with a dementia to perceive a false step.
	The tone-on-tone design is subtle and consistent across all Geotone QuickLay shades.
6: Reduce sparkle	The blended colours are tonally close creating an almost plain pattern and the matt surface finish for even distribution of light reflectance, helps reduce any unwanted glare, sparkle or shimmer.
7: Promote the use of a matt floor finish	Geotone QuickLay is a matt flooring, and this will help reduce any unwanted glare from natural sunlight, from nearby windows, or artificial lighting.
8: Blend flecks with the tone of the main floor surface	The blended decoration, small in scale is uniform in its allocation reducing any issues which may have arisen from having a larger scale, uneven, random decorative finish.
9: Avoid unpleasant smells and odours	People living with a dementia may have a strong emotional reaction to smells and odours which can lead to confusion and stress and so cleaning & disinfecting of floor coverings is paramount.
	Featuring a polyurethane reinforcement and combined with a superior closed surface finish, this enhanced protection allows the use of a polish-free maintenance regime for the lifetime of the Geotone QuickLay flooring. Additionally, adhesive-free flooring installation is characterized by no contamination of sensitive areas by dust or associated odours.
10: Provide good transition between differing floor finishes	Correct installation of edging strips minimises problems such as water leakage and trip hazard. Where flooring with a raised emboss is used, ensure that its use is limited to areas where additional safety flooring is required, such as wet rooms and barefoot areas.





Visually Accessible Spaces

When creating inclusive, safe, calm and supportive dementia-led environments, LRVs, NCS and DSDC ratings provide guidance on the reasonable provisions which should be made for people to access and use a building as per Building Regulations.

Geotone QuickLay has met the standards of DSDC Product Accreditation, University of Stirling's Dementia Services Development Centre, awarded Class 1b (17 shades) and 2 rating (1 shade) for dementia design.

Product & weld rod	NCS Reference	LRV's	dsdc Rating
Periwinkle Pink 6280	1015-R20B	64	1b
Glacial Mist 6281	1505-Y20R	62	1b
Pearl Grey 6271	1502-B	62	1b
Prehnite 6278	1510-G40Y	60	1b
Sand Bar 6284	1510-Y40R	59	1b
Alpine Blue 6274	1020-R80B	53	1b
Pebble Time 6267	2500-N	49	1b
Shingle Beach 6282	3005-Y20R	43	1b
Flint Earth 6272	2010-B	42	1b
Toasted Mauve 6285	2020-R60B	40	1b
Aventurine 6279	3020-G30Y	32	1b
Fountain Stone 6268	4500-N	31	1b
Classic Rock 6273	4502-B	26	1b
Volcanics 6283	5005-Y20R	25	1b
Solent Gold 6286	3040-Y50R	25	1b
Paddlestone 6276	3030-R90B	28	1b
Star Sapphire 6277	5030-R90B	13	1b
Magnetite 6269	7500-N	10	2

Totally matt flooring. This will help reduce any unwanted glare from natural sunlight from nearby windows or from artificial lighting. Decorative effect is very small in scale and uniform in its allocation. These colours are tonally close creating an almost plain pattern & can be used throughout.*

Magnetite 6269 has been rated 2 due to the dark colour (LRV 10).*

2

*Bear in mind the need to contrast flooring with walls, skirtings, doors / frames, furniture & sanitary ware. A minimum contrast of 30 units LRV (Light Reflectance Value) is recommended between surfaces

The Collection

Design & decoration

Visually, the design concept for Geotone QuickLay centres around a common colour scheme, taking inspiration from elements found in the natural world, including pebbles and stones, often linked to forms of wellbeing & comfort.

Colour communication

Each shade features a monochromatic colour scheme and is made up of different tones of a single colour that brings into focus the depth and texture of each blended colourway.

Tone-on-tone Geotone QuickLay, with a matt surface finish, evokes a sense of calm and rejuvenation across the broad palette.

With a dedicated NCS value - Natural Colour System® - the global go-to standard for defining and communicating colours - the same colour can be reproduced across a variety of materials.

Lightness & brightness of colour

While NCS describes the visual characteristics of a colour, Light Reflectance Value (LRV) measures the proportion of useful light reflected by an object.


A universal value for visual 'contrast', LRVs help determine the level of contrast between floors, walls and doors. A requirement within Building Regulations, this ensures equal and safe access for visually impaired people and for those living with a dementia.

Maximising the benefits of PUR

Geotone QuickLay incorporates a polyurethane reinforcement, PUR, which protects the floor covering by resisting soiling and scuffing and allows the use of a polish-free maintenance regime, for the lifetime of the flooring.







Fountain Stone

LRV 31 w/r 6268

NCS S 4500-N

Flint Earth

LRV 42 w/r 6272

NCS S 2010-B

6269


Magnetite

LRV10 w/r6269

NCS S 7500-N

w/r - Weld Rod










Pearl Grey


LRV 62 w/r 6271












Paddlestone

LRV 28 w/r 6276




6282

Shingle Beach

LRV 43 w/r 6282

NCS S 3005-Y20R



6283

Volcanics

LRV 25 w/r 6283





6274

Alpine Blue

LRV 53 w/r 6274

NCS S 1020-R80B

6278

Prehnite

LRV 60 w/r 6278

NCS S 1510-G40Y



Aventurine

LRV 32 w/r 6279

NCS S 3020-G30Y



6280

Periwinkle Pink

LRV 64 w/r 6280

NCS S 1015-R20B



Solent Gold

LRV 25 w/r 6286

NCS S 3040-Y50R

LRV - Light Reflectance Value

NCS - Natural Colour System

Sustainable Performance

At Polyflor we are constantly reviewing alternatives and new ideas to improve our environments.

Through modern manufacturing practices, vinyl has a low environmental impact. Combined with exceptional functionality and performance characteristics, across many applications and sectors, vinyl is an environmentally sound choice.

Our Goal: Contribution to the Built Environment

To develop 'loose lay' (adhesive-free) products with reduced environmental impact for ease of recycling.

Geotone QuickLay

From ease of installation to its in-use phase of excellent indoor air quality and low VOC emissions, plus the opportunity to both reuse and recycle, Geotone QuickLay is the sustainable solution for quick turnaround projects.

Our commitment to the Health & Care sector

Polyflor is a recommended supplier to the NHS ProCure23 (P23) framework

With a rich history of supplying UK manufactured products to the NHS from our manufacturing sites in Manchester and Stockton-on-Tees, collaborating with the framework's Principal Supply Chain Partners, our aim remains to continue to deliver best value flooring solutions to the NHS.







Geotone QuickLay Technical Information

Product Format	Standard	Result	
Gauge	ISO 24346 (EN 428)	2.2mm	
Total Weight	ISO 23997 (EN 430)	2700g/m²	
Finish		PUR	
Sheet Size	Size	Shades	Coverage per Roll
Sheet	2m x 20m	18	40 m²
Performance Requirements	Standard	Result	
General Performance	ISO 10582 ASTM F1303	Conforms Type II, Grade 1, (Class B Backing
Use Area	ISO 10874 (EN 685)	34,42	
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 Appendix D ASTM D2047	Class DS R10 R10 SCOF ≥0.5	
Binder Content	ISO 10582	Type I	
Abrasion Resistance	EN 660-2	Group T	
Reaction to Fire	EN 13501-1 ASTM E648 CAN/ULC S-102.2 AS ISO 9239-1	Class Bfl-S1 Class 1 FSV < 300; SDV Complies	< 500
Static Electrical Propensity	EN 1815	≤2.0kV Classifie	d as 'antistatic'
Residual Indentation	ISO 24343-1 ASTM F970 (Modified) ASTM F1914	≤0.10mm ≤0.005" (750psi ≤0.005")
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable	
Furniture Leg	ISO 16581 (EN 424)	Complies	
Flexibility	ISO 24344 (EN 435) ASTM F137	(Method A) Pass 20mm ø 0.25" Pass	
Underfloor Heating		Suitable, max 27	°C
Dimensional Stability	ISO 23999 (EN 434)	≤0.40%	
Light Fastness	ISO 105-B02 (Method 3)	≥6	
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets	
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets	
Sustainability	Standard	Result	
Recyclable & Reusable		100%	
Recycled Content		Contains recycle	d material
REACh		Compliant	
Indoor Air Comfort Gold		Eurofins certified	d product
FloorScore		Certified	
Finnish M1 Classification		Certified	
Acoustic Performance	Standard	Result	
Impact Sound Reduction	ISO 10140-3	6dB	
Maintenance Performance	Standard	Result	
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance	
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels		
Steam Cleaning	Suitable for steam cleaning on a periodi	r hasis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Hygiene	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth

Designed for Healthcare:

Welcome

Hospital waiting areas put visitors first. Offering a safe & welcoming space, with access to a variety of seating areas and information, Geotone QuickLay is the solution.







projects







6274





6273 Classic Rock

NCS S 4502-B

6267 Pebble Time

LRV 49 w/r 6267 NCS S 2500-N

6276 Paddlestone

LRV 28 w/r 6276 NCS S 3030-R90B

Alpine Blue LRV 53 w/r 6274 NCS S 1020-R80B

Designed for Aged Care:

Living well

Aged care facilities put residents first. Offering a safe, supportive and motivational space, Geotone QuickLay is the solution.






emissions













6281 Glacial Mist LRV 62 w/r 6281

NCS S 1505-Y20R

LRV 32 w/r 6279

NCS S 3020-G30Y

6278 LRV 60 w/r 6278

NCS S 1510-G40Y

6283 Volcanics

LRV 25 w/r 6283 NCS S 5005-Y20R

Designed for Education:


Think about things differently

An art college space puts students first. Offering an open and airy, inspirational space, Geotone QuickLay is the solution for that creative vibe.

















6269

LRV 31 w/r 6268

6273 Classic Rock

LRV 26 w/r 6273


6271 Pearl Grey

LRV 62 w/r 6271

Designed for Retail:

Time to shop

Retail environments put the customer journey first. Offering an inviting, engaging retail space, Geotone QuickLay is the solution.






Suitable for high traffic areas

Immediate weld for a seamless finish











6282 Shingle Beach LRV 43 w/r 6282

NCS S 3005-Y20R

LRV 25 w/r 6286

NCS S 3040-Y50R NCS S 3020-G30Y

6279 LRV 32 w/r 6279

Glacial Mist LRV 62 w/r 6281 NCS S 1505-Y20R

Designed for Leisure:

Time to relax

Hospitality puts customer service first. Offering a welcoming, relaxing space, Geotone QuickLay is the solution.







Superior

Low VOC emissions cleanability











6285 Toasted Mauve

NCS S 2020-R60B

LRV 40 w/r 6285 LRV 64 w/r 6280

NCS S 1015-R20B

6272 Flint Earth LRV 42 w/r 6272 6271 Pearl Grey

LRV 62 w/r 6271 NCS S 1502-B

POLYFLOR™ INTERNATIONAL

Australia

Polyflor Australia Tel: 1800 777 425

Email: sales@polyflor.com.au

Polyflor Canada Inc. Tel: +1 905 364 3000 Email: sales@polyflor.ca

Polyflor North Asia Ltd Tel: +(852) 2865 0101 Email: info@polyflor.com.hk

Colombia

Polyflor Ltd. (LATAM Office) Tel: +57 3142859005 Email: export@polyflor.com

James Halstead France SAS Tel: +33 (0)8 20 20 32 11 Email: info@jhfrance.fr

Germany objectflor Art und Design Belags GmbH Tel: +49 (0) 2236 966 330 Email: info@objectflor.de

Ireland

Polyflor Ireland Tel: +353 (1) 864 9304 Email: salesireland@polyflor.com

Malaysia

Tel: 1300 80 7788 Email: sales@polyflor.com.my

Middle East

Polyflor Ltd. Tel: +971 50 406 8114 Email: export@polyflor.com

New Zealand

Polyflor New Zealand Ltd. Tel: 0800 765 935 Tel: +64 9 269 1111 Email: sales@polyflor.co.nz

Norway

Polyflor Nordic Tel: +47 23 00 84 00 Email: firmapost@polyflor.no

Spain

Polyflor Ltd. Tel: +34 619 949 054 Email: export@polyflor.com

Sweden

Polyflor Nordic Sweden AB Tel: +46 (0) 300 15820 Email: info@polyflor.se

POLYFLOR™ UK

Polyflor Ltd. PO Box 3, Radcliffe New Road Whitefield, Manchester, M45 7NR

UK Sales Direct: +44 (0) 161 767 1122 Export Sales Direct: +44 (0) 161 767 1913 Technical Support: +44 (0) 161 767 1912 Reception: +44 (0) 161 767 1111 Email: info@polyflor.com



