

Secura PUR

PRODUCT SPECIFICATION

Key Features

- > Wood, parquet & stone designs
- > Loose lay luxury vinyl sheet
- > Available in 2m, 3m & 4m roll widths
- > 19dB acoustic performance
- > Light commercial & residential



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	3.0mm
Wear Layer	ISO 24340 (EN 429)	0.35mm
Total Weight	ISO 23997 (EN 430)	1780g/m ²
Finish		PUR

Sheet Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	4m x 20-25m	18	-	80-100m ²
	3m x 20-25m	18	-	60-75m ²
	2m x 20-25m	18	-	40-50m ²

Performance Requirements	Standard	Result
General Performance	ISO 26986 (EN 653)	Conforms
Use Area	ISO 10874 (EN 685)	23, 32, 41
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B	Class DS R10
Abrasion Resistance	EN 653	Group T
Reaction to Fire	EN 13501-1	Class Bfl-S1
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1	≤0.20mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Furniture Leg	ISO 16581 (EN 424)	Pass
Dimensional Stability	ISO 23999 (EN 434)	≤0.40%
Flexibility	ISO 24344 (EN 435)	(Method A) Pass 20mm ø
Thermal Resistance	EN 12667	0.0525m ² K/W 0.525 Tog
Underfloor Heating		Suitable, max 27°C
Light Fastness	ISO 105-B02 (Method 3)	≥6

Sustainability

	Standard	Result
BRE Green Guide		A+ ENP 415
Generic EN 15804 EPD		Available
Recyclable & Reusable		100%
Recyclable Content		10%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

Acoustic Performance

	Standard	Result
Impact Sound Reduction	ISO 10140-3	19dB

Maintenance Performance

	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



BS EN 14041



EN 14041


Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com


© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1

RANGE SHADES



Oakland Parquet 2167
 plank size in sheet: 88 x 700mm
 LRV 38



Grey Oak Parquet 2168
 plank size in sheet: 88 x 700mm
 LRV 37



White Limed Ash 2160
 plank size in sheet: 166 x 1500mm
 LRV 57




Coastal Oak 2159
 plank size in sheet: 200 x 1500mm
 LRV 37




Sterling Oak 2161
 plank size in sheet: 200 x 1000mm
 LRV 40



Blond Oak 2127
 plank size in sheet: 200 x 1500mm
 LRV 42




Golden Oak 2128
 plank size in sheet: 62.5 x 500-1000mm
 LRV 37




Wheatfield Oak 2163
 plank size in sheet: 167 x 1500mm
 LRV 39




Natural Oak 2126
 plank size in sheet: 200 x 1000mm
 LRV 32




Honey Blushed Oak 2162
 plank size in sheet: 200 x 1500mm
 LRV 30




Country Oak 2130
 plank size in sheet: 200 x 1500mm
 LRV 20




Antique Herringbone 2129
 plank size in sheet: 140 x 710mm
 LRV 20




Ebony 2135
 plank size in sheet: 100-150 x 1000mm
 LRV 12




Limestone 2111
 plank size in sheet: 333 x 500mm
 LRV 55




Powdered Concrete 2164
 NCS S 3000-N
 LRV 40



Polished Concrete 2118
 NCS S 5502-Y
 LRV 23



Plymouth Slate 2165
 plank size in sheet: 333 x 500mm
 LRV 18



Black Slate 2114
 plank size in sheet: 333 x 500mm
 LRV 8

LRV - Light Reflectance Value

NCS - Natural Colour System

Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1